

# RV11



The rugged revolution continues

Following the success of the RS11 now comes the RV11, a 15,6" slim yet fully rugged computer using the same design as the RS11

Without sacrificing any of its rugged performance for military applications, just as the RS11, the RV11 packs all the performance needed, and more. With main features such as an Intel i7-3517UE CPU, Intel HD graphics 4000, SATA III SSD and up to 8 GB RAM, the user will have all the performance required in a highly rugged and slim package.

Just as its little brother, the RS11, the RV11 is designed for extreme environments and is made to be used in the field. MIL-STD-810G and IP65\* certification is standard.

Guaranteed performance

Products supplied by MilDef Crete are always provided with lifetime support to ensure that the equipment maintains peak performance over many future missions.

# RV11

## Technical Specification

CPU	Intel Core i7-3517UE 1.7 GHz (Max Turbo Boost Frequency 2.8 GHz)
RAM	Max 8 GB DDR3 1600 MHz
Graphic	Intel HD Graphics 4000
Storage	120 GB - 500 GB SATA III SSD (removable)
Display	15.6" Widescreen (1920 x 1080), Full HD, optical bonding, LCD with LED backlight
Sound	HD Audio and stereo speakers Embedded digital mic
Keyboard/mouse	87-key with Backlight, Capacitive Touchpad with multi-touch, works with gloves (Win 8 compatible)
Interfaces (right)	1 x SSD Bay
Interfaces (left)	1 x SD Card Slot (supports SDHC/SDXC) 1 x SIM Card Slot 1 x USB 3.0 (USB-IF BC V1.2 for 1.5A fast charger) 1 x USB 3.0 1 x GigaLAN RJ45
Interfaces (rear)	1 x MIL DC in Optional 1-6 mil connectors (Fischer)
Interfaces (bottom)	1 x Multi bay port: - 1 x PCI-e - 1 x USB3.0 - 1 x USB 2.0 - 1 x Power (VBATA/1A & 5V/1A)
Primary Battery	Removable 11.1V / 6040mAh Li-Polymer battery
Power Input	AC Adapter 90W AC 100-240V 50/60Hz MIL DC-in 12- 32V with Surge Protector
Case	CNC milled Aluminum (Colors available in black or green)
Dimensions	382 x 295 x 25 mm (W x D x H, w/o corner rubbers) 386 x 299 x 32 mm (W x D x H, with corner rubbers)
Weight	3.7kg – Depending on configuration
Certifications	CE, FCC, WEEE, REACH, IP65 (open port, without caps), MIL-STD-810G* and MIL-STD-461F*, RoHS2.0, Explosive Atmosphere/Solar Radiation Test
OS	Windows 7, 8 and 10

\*Contact **MilDef Crete** for full specifications of MIL-STD-810G and MIL-STD-461F

MIL-STD-810G	Operating	Storage
Altitude Method 500.5, ( <i>procedure I, II</i> )	4572 m (15000 ft)	12192 m (40000 ft)
Temperature Method 501.5 & 502.5, ( <i>procedure I, II</i> )	-20 °C to 60 °C (-4 °F to 140 °F)	-40 °C to 70 °C (-40 °F to 158 °F)
Temp Shock Method 503.5 ( <i>procedure I</i> )	-20 °C to 60 °C (-4 °F to 140 °F)	-
Shock Method 516.6, ( <i>procedure I</i> )	40 G, 11 ms	40 G, 11 ms
Vibration Method 514.6, ( <i>category 1, 14 &amp; 20</i> )	M548 Tracked Vehicle, OH58A/C Helicopter and Composit wheeled vehicle vibration	-
Rain Method 506.5, ( <i>procedure II</i> )	276 kPa, 5 Surfaces, 40 min/Surface	-
Humidity Method 507.5	-	Ten 24 h test cycles
Salt Fog Method 509.5, ( <i>procedure I</i> )	-	Salt 5 ±1 %, 24 h wet + 24 h dry/cycle. Total 2cycles / 96 h

## Standard Options

Communications	1 x 2 <sup>nd</sup> LAN RJ45 (GigaLAN) 1 x MIL LAN 1 x MIL VGA 1-2 x MIL COM 1 x MIL Audio 1 x MIL USB GPS WLAN (a/b/g/n) / BT 4.0 (BLE) WWAN <i>HSPA 3G</i>
Additional Connectivity	1 x Mini HDMI
Mouse	Resistive touchpad
Display	1000 Nits
Temperature	-30 °C
MIL-STD-461F	Ground Navy, Ground Army



www.mildef.com.tw